

# Auto-Dialers







## COMBI BOX GSM

Car roof auto-dialer with hands-free, GSM and battery integrated, ideal for modernization.

### MAIN FEATURES

- Integrated intercom (Full-duplex, maximum speaker power 3W).
- Integrated GSM modem.
- Buffer battery management and efficiency test.
- Technical alarms: power supply presence, low and/or efficient battery.
- 1 output relay enabled by remote or alarm event.
- Protocols Management for call-center (ex. Ademco Contact ID, P100).
- Simplified wiring system for speaker modules (Speakerlift) 2 wires
- Programming by telephone keypad; locally and remotely.
- Programming via graphic display DISP903.
- Programming via Vegacom APP
- Memory capacity up to 10 phone numbers.
- 32 customizable messages divided into 4 languages.
- Inductive loop facility for the hard-of-hearing.
- 4 types of inputs: alarm input, alarm filter input, technical alarm input and reset alarm input.
- Sent and acknowledged alarm signals.
- External antenna with magnetic base and 2mt of wire.
- Cable with microphone, length 2mt.

### BENEFITS

	INTEGRATED HANDS-FREE KIT
	BATTERY LEVEL CONTROL
	SIMPLIFIED WIRING SYSTEM
	APP FOR PROGRAMMING

**SIZE**  
162x121x65mm

### TECHNICAL DATA

Input power supply: 220Vac 50Hz.  
Output power supply: 12V dc 500mA.  
Inputs: 4x opto isolator 5-50V 50 mA.  
Outputs: 1x Relè, 2x Open Collector.  
GSM radio module: Quad-band 850/900/1800/1900 MHz.  
GPRS radio module: class 12.

### CODES

COMBI BOX GSM-I: auto-dialer with Italian power plug.  
COMBI BOX GSM-T: auto-dialer with Schuko power plug.  
COMBI BOX GSM-UK: auto-dialer with British power plug.  
COMBI BOX GSM-FIL: auto-dialer with free wires.